



# Storage Instructions

- for PVC and PUR coated products and foils -

- Before using, the material should be stored for 24 hours at ambient temperature, in order to avoid differences in warming and to guarantee steady process parameters. (Preferably, the material is stored at processing conditions.)
- Storage areas with high humidity as well as external bearing should be avoided. The rolls may not be exposed to liquids, chemicals, disinfectants or detergents.
- The storage in an enclosed space with 30-70% humidity and 20°C +/- 10°C, must not exceed 24 months.
- The delivered material must be protected from direct sunlight..
- Any kind of pressure or contact with hard, sharp-edged or peaked objects must be avoided.
- It is essential for storage that the product can clearly be identified by the label
- Explanations of the different details shown on our label can be found in the figure below.
- The FIFO-principle ( First In First Out) must be observed.

**When processing an object only material from one production batch should be used.**

VOWALON Beschichtung GmbH Bahnhofstraße 46 D - 08233 Treuen Tel: + 49(0)37468-600      Mail: info@vowalon.de			
Materialbezeichnung - part description			
PISA ATOLL		← colour name	
Materialnr. - article no.			
003600		← order number	
Kundenbez. - clients ref.			
Kommission (R) - batch no.			
2205273		← commission/ production batch	
Rollennr. - roll no.			
6234030		← roll number	
Fert. - Datum - inspection date	Inspector	Artikel - article	
18.06.2022	06892	P3392P	
Menge brutto - gross quantity		Menge netto - net quantity	
m	25,00	25,00	← material number
qm	35,00	35,00	
Stück - quantity	1	Breite - width in m	1,40

Made in Germany